

---

**vinylpublic - Technical information**

---

Application areas	EN 685	21-33 And 42
Chemical resistance	EN 423	Approved
Castor load	EN 425	Approved
Indentation resistance	EN 433	0.05 mm or less
Dimensional stability	EN 434	<0,25%
Flexibility	EN 435	Approved
Wear resistance	EN 660	Group T reduced thickness 0.068 mm
Friction	DIN 51130	R9
Noise damping	DIN 52210	4 dB
Light fastness	ISO 2105 B02	> 6
On under floor heating		Yes, max +27°
Fire rating	EN 13501-1	B – S1

**Warranty:**

Idé Flooring Sverige AB. offer a **10-year warranty** from date of purchase provided the flooring has been laid and installed by a professional in accordance with our recommendations and written specifications.

- Faults found in the material prior to laying should be reported immediately to the distributor/dealer where purchased.
- Faulty goods will be replaced free of charge.
- If it is not possible to replace the panels or repair is not economically viable, a refund will be given.

**The warranty does not cover the following:**

- Floors that have been poorly laid/maintained.
- Damage arising from chemicals or movement in sub-floors.
- Damage occurring as a result of cuts, splits, scratches, burns, indentations from stiletto heels, stains, accidents or damage occurring through other than normal use of the product.
- Consequential damage occurring because the floor was laid incorrectly or as a result of other work carried out incorrectly.
- Any inconvenience or damage caused by an uneven or unsuitable subfloor or by moisture, hydraulic pressure or alkali on the subfloor.

*If there is a dispute on a claim we reserve the right to authorise a qualified impartial inspector to arbitrate between parties.*