

wineo

THAT'S FLOORING



wineo 1500

PURLINE ORGANIC FLOORING

**BEST INGREDIENTS FOR  
EVERY CHALLENGE**

# THAT'S FLOORING

## CONTENT

Best ingredients	04
wineo PURLINE organic flooring	06
Product advantages	08
Further product advantages	10
Lifecycle cost analysis	12
Application areas	14
Formats	16
Surface structures	17
Product composition	18

### Collections

<b>wineo 1500</b> wood XS   L   XL	20
<b>wineo 1500</b> stone XL	40
<b>wineo 1500</b> wood	44
<b>wineo 1500</b> chip	56
<b>wineo 1500</b> fusion   fusion XL	66
<b>wineo 1500</b> fusion combinations	70

### Special solutions

<b>wineo 1500</b> special products	72
<b>wineo 1500</b> customised	73
<b>wineo 1500</b> safety	74
<b>wineo 1500</b> rail	76
<b>wineo 1500</b> sea	77

PERFECT FIT Accessories	78
Service	80
Certifications	82
Collection overview	84



## BEST INGREDIENTS FOR CREATIVE RESULTS

**Unbeatably ecological, limitlessly creative and extremely resilient – that's the wineo 1500 collection.**


wineo PURLINE organic flooring is probably the most ecological, resilient flooring available on the market. Without the addition of chlorine, without plasticisers and without solvents: wineo PURLINE organic flooring impresses not only with its incomparable sustainability, but also with its impressive hard-wearing features and range of designs.

# THE NEXT GENERATION OF SUSTAINABLE FLOORING

wineo PURLINE organic flooring is a high-quality polyurethane flooring solution made from the finest materials. The basis is provided by ecuran, a high-performance composite material that is manufactured primarily from plant-based oils such as canola oil or castor oil and naturally-occurring mineral components such as chalk. Without the addition of chlorine, without plasticisers and without solvents: wineo PURLINE organic flooring impresses most of all with its sustainability, combined with its extreme hard-wearing features. It is also completely PVC-free and 100% Made in Germany.



**MADE IN GERMANY**



## SUSTAINABILITY

because that's what we believe in

- with the high-performance composite material ecuran
- usage of renewable raw materials and natural fillers
- absolutely uncritical to dispose
- environmentally award-winning (see pages 72/73)
- completely odour-neutral
- without the addition of chlorine, without plasticisers and without solvents
- PVC-free

## HIGH-PERFORMANCE

for everyday use

- tested resilience
- for domestic through to light industrial use
- low lifecycle costs
- UV-resistant and temperature-stable
- outstanding residual indentation performance in combination with an excellent reset behaviour

## CASTOR OIL

**Plant oils replace the majority of petrochemical polyols in the polyurethane formulation. Castor oil, extracted from castor beans, mostly comes from India and is typically grown by small-scale farmers who also use it as a protective plant for agricultural land. Castor oil plant cultivation is socially responsible; it is not grown in monocultures or on cleared land and does not compete with food farming. Similarly high criteria apply to alternative plant oils. Windmüller processes over 7,000 tonnes of castor oil every year. wineo has recently joined the first global programme for the sustainable cultivation of castor beans.**

Find out more at [en.wineo.de](http://en.wineo.de)

## DID YOU KNOW?

## DESIGN DIVERSITY

because it catches the eye

- more than 150 decors across three collections
- different formats
- for gluing and clicking in
- on the roll or as planks
- modern, colourful and creative designs
- authentic-looking surface
- all-round V4 joint (V4)
- wood decors on rolls with a repeat length of up to 4.50 m

# BEST INGREDIENTS FOR MAXIMUM PERFORMANCE

Sustainable can also be particularly efficient – wineo 1500 not only consists of the best ingredients, but also withstands a lot. It's simply high-efficiency flooring for heavily stressed areas of application.

## 5X BETTER



### EXTREMELY DURABLE

Even after 25,000 crossings with 500 kg at 6 km/h, wineo 1500 seems completely unaffected. This was proven by Bielefeld University of Applied Sciences (FH), which even certified the product's suitability for deployment in the light industry. In addition to this, the high-efficiency flooring excels with an outstanding residual indentation behaviour of  $\leq 0,10$  mm in accordance with EN ISO 24343-1.



### OUTSTANDINGLY UV-RESISTANT

Compared with other floorings in its class, wineo 1500 has a high light fastness of  $\geq 7$ . The EN 105 – B02 hereby certifies the presence of excellent UV resistance.



### PARTICULARLY TEMPERATURE STABLE

wineo 1500 can also withstand changes in climatic conditions, for example a rise in room temperature. The EN ISO 23999 confirms the high dimensional and thermal stability of the flooring.



### ABSOLUTELY ODOUR NEUTRAL

TÜV Proficert, a certification agency, confirms that wineo 1500 flooring remains odour neutral throughout both the installation process and its use thereafter. There are no disturbing odours.



### EXCEPTIONALLY ECONOMICAL

Substantial savings can be achieved in terms of cleaning and resource costs. Approximately 30% is saved as a result of extremely low lifecycle costs, making the wineo 1500 exceptionally economical. This was certified by the Pfiff Institute (page 12).

## BEST INGREDIENTS FOR OPTIMUM ATTRIBUTES

wineo 1500 not only looks good in every situation, it can also withstand a lot. That's convincing.



### INDOOR AIR QUALITY

Take a deep breath: PURLINE organic flooring emits **no harmful substances** into the atmosphere.



### EASY CARE

The polyurethane surface makes the wineo 1500 **easy to clean**.



### MINIMAL SMOKE

Even in case of fire: **Low smoke density**. **Escape routes** remain **more visible**.



### NON-SLIP

The tested surface ensures **safety with every step**.



### QUIET

The soft surface ensures pleasantly **quiet acoustics**.



### SUITABLE FOR HIGH HUMIDITY AREAS

In the **kitchen or bathroom**: wineo 1500 shows its best side in every situation.



### WARM TO THE FEET

The organic flooring **feels pleasantly warm** and is perfect for lounging, playing and living.



### GENTLE ON THE ANKLES

**Health conscious**: The elastic surface is gentle on the joints.



### SUITABLE FOR UNDERFLOOR HEATING

More comfort: Installed over underfloor heating, the wineo 1500 provides **additional cozy warmth**.

## BEST INGREDIENTS FOR LOW COSTS

Resistant to chemical and mechanical stresses, environmentally compatible and particularly easy to clean: wineo PURLINE organic flooring's lifecycle costs are considerably lower than those of all other conventional flooring solutions currently on the market. This has also been confirmed by the Memmingen-based Pfiff Institute for applied industrial cleaning technology.


This is especially evident in heavily frequented areas such as medical institutions, department stores, schools, airports or other public buildings. wineo PURLINE organic flooring proves to be particularly hard-wearing and economical.

## WHAT THE PFIFF INSTITUTE HAS TO SAY:

- conventional cleaning agents can be used without problems
- the closed surface makes cleaning particularly easy
- additional polishing or initial care is unnecessary
- all surface disinfectants can be used
- various tests demonstrate an effective disinfectability
- contrast agents normally used in hospitals do not discolour the organic PU flooring
- no impressions left by furniture after a brief regeneration
- no visible wear and tear resulting from mechanical stress
- highly resistant to direct sunlight

Source: Pfiff Institute for applied industrial cleaning technology, January 2013

PURLINE  
ORGANIC  
FLOORING





RECOMMENDED FOR  
**HEALTHCARE**

University Clinic Münster (UKM)  
wineo 1500 fusion | cool.one



RECOMMENDED FOR  
**EDUCATION AND PUBLIC BUILDINGS**

Zernike College  
wineo 1500 chip | Silver Grey

Foto: Mark Hadden



RECOMMENDED FOR  
**STORE BUILDING**

Fashion store Vockeroth  
wineo 1500 stone XL | Just Concrete



RECOMMENDED FOR  
**APARTMENT BUILDING**

Apartment Linda | First Retail Consulting  
wineo 1500 wood XS | Garden Oak



RECOMMENDED FOR  
**HOTELS AND RESTAURANTS**

Inside-Hotel Wolfsburg  
wineo 1500 stone XL | Just Concrete



RECOMMENDED FOR  
**OFFICE AND ADMINISTRATION BUILDINGS**

kohlhaas GmbH & Co. KG  
wineo 1500 wood | Floating Wood Snow



# THE SUITABLE FORMAT FOR EVERY APPLICATION


Roll format or practical planks? Both have their individual advantages, are extremely practical for renovation work due to their low structural height of 2.5 mm and have ideal installation attributes.



The flooring for large surfaces – delivered in the standard format 20 × 2 m and to be cut simply using a hook blade. For the ideal installation we recommend fibre-based adhesives.



wineo 1500 as a plank or tile solution is an ideal choice when it comes to individual designs. The XS, L and XL formats can be installed together and thereby offer maximum scope for design options.



wood XS  
600 × 100 mm

wood L  
1200 × 200 mm

wood XL  
1500 × 250 mm

stone XL | fusion XL  
1000 × 500 mm

# THE ORGANIC FLOORING WITH STRUCTURE


wineo 1500 has a variety of surfaces that are coordinated with the designs. The embossed stone and wood structures provide maximum authenticity. Reference to the respective surfaces can be found under the decor illustration on the following collection pages.



Elegant wood structure



Fine wood structure



Pine structure



Slate structure



Soft structure



**WINEO 1500  
FOR MORE SAFETY**  
Thanks to its special surface texture, the R10 offers maximum slip resistance and safe standing in every situation.

R10

# PRODUCT COMPOSITION


The inner values are, of course, also crucial. wineo 1500 is convincing in this area too with its best ingredients based on the ecuran organic formula. The suitable insulation mat for maximum walking noise reduction is available as an optional extra.

## wineo 1500

wood XS | wood L | wood XL | stone XL | wood | chip | fusion | fusion XL | safety



- 1 Top element**  
PU-top layer with surface structure, decor paper & stabilisation
- 2 Base layer**  
ecuran high-performance composite material
- 3 Backing**  
integrated FleeceTEC-System® for easy and comfortable installation



Newport Oak Natural | Jade Green  
wineo 1500 chip | PLR393C  
wineo 1500 chip | PLR373C



**wineo 1500**  
wood XS | L | XL

## BEST INGREDIENTS FOR CREATIVE RESULTS


wineo 1500 wood convinces with 36 modern and classic wood designs. The three attractive formats offer a range of creative installation options, which range from fish bone to extravagant installation designs.

# wineo 1500 wood XS

- Installation type:** Glue
- Format:** 600 × 100 mm
- Product thickness:** 2.5 mm
- Content / box:** 28/1.68 m<sup>2</sup>



Installed area with the Garden Oak and Island Oak Moon example



**Pure White** | PL025C | Elegant wood structure



**Pure Black** | PL194C | Elegant wood structure



**Garden Oak** | PL005C | Elegant wood structure



**Island Oak Moon** | PL045C | Elegant wood structure



Garden Oak | Island Oak Moon  
 wineo 1500 wood XS | PL005C  
 wineo 1500 wood XS | PL045C

## wineo 1500 wood L

**Installation type:** Glue  
**Format:** 1200 × 200mm  
**Product thickness:** 2.5mm  
**Content / box:** 20/4.8m<sup>2</sup>



Installed area Wild Wood



Wild Wood | PL100C | Soft structure

## wineo 1500 wood L

**Installation type:** Glue  
**Format:** 1200 × 200mm  
**Product thickness:** 2.5mm  
**Content / box:** 20/4.8m<sup>2</sup>



Installed area Uptown Pine



Uptown Pine | PL083C | Fine wood structure



Installed area Noble Elm



Noble Elm | PL081C | Fine wood structure

## wineo 1500 wood L

**Installation type:** Glue  
**Format:** 1200 × 200mm  
**Product thickness:** 2.5mm  
**Content / box:** 20/4.8m<sup>2</sup>



Installed area Canyon Oak with the Canyon Oak Sand example



Canyon Oak Sand | PL075C | Elegant wood structure



Canyon Oak Honey | PL076C | Elegant wood structure

## wineo 1500 wood L

**Installation type:** Glue  
**Format:** 1200 × 200mm  
**Product thickness:** 2.5mm  
**Content / box:** 20/4.8m<sup>2</sup>



Installed area Classic Oak with the Classic Oak Winter example



Classic Oak Winter | PL074C | Elegant wood structure



Classic Oak Autumn | PL073C | Elegant wood structure



Classic Oak Summer | PL072C | Elegant wood structure



Classic Oak Spring | PL071C | Elegant wood structure060602

## wineo 1500 wood L

**Installation type:** Glue  
**Format:** 1200 × 200mm  
**Product thickness:** 2.5mm  
**Content / box:** 20/4.8m<sup>2</sup>



Installed area Supreme Oak with the Supreme Oak Grey example



Supreme Oak Grey | PL070C | Fine wood structure



Supreme Oak Silver | PL069C | Fine wood structure



Supreme Oak Natural | PL068C | Fine wood structure

## wineo 1500 wood L

**Installation type:** Glue  
**Format:** 1200 × 200mm  
**Product thickness:** 2.5mm  
**Content / box:** 20/4.8m<sup>2</sup>



Installed area Polar Pine



Polar Pine | PL082C | Pine structure



Installed area Pure Pine



Pure Pine | PL079C | Pine structure

# wineo 1500 wood L

**Installation type:** Glue  
**Format:** 1200 × 200mm  
**Product thickness:** 2.5mm  
**Content / box:** 20/4.8m<sup>2</sup>



Mixed Decors = various plank colours in one box



Silver Pine Mixed (Installed area) | PL078C | Pine structure



Golden Pine Mixed (Installed area) | PL077C | Pine structure




Golden Pine Mixed  
 wineo 1500 wood L | PL077C



## wineo 1500 wood XL

**Installation type:** Glue  
**Format:** 1500 × 250mm  
**Product thickness:** 2.5mm  
**Content / box:** 12/4.5m<sup>2</sup>



**Installed area Crystal Pine** | lacquered, all around V4 joint



**Crystal Pine** | PL098C | Elegant wood structure | lacquered, all around V4 joint

## wineo 1500 wood XL

**Installation type:** Glue  
**Format:** 1500 × 250mm  
**Product thickness:** 2.5mm  
**Content / box:** 12/4.5m<sup>2</sup>



**Installed area Native Ash** | lacquered, all around V4 joint



**Native Ash** | PL099C | Elegant wood structure | lacquered, all around V4 joint



**Installed area Crafted Oak** | lacquered, all around V4 joint



**Crafted Oak** | PL080C | Elegant wood structure | lacquered, all around V4 joint

## wineo 1500 wood XL

**Installation type:** Glue  
**Format:** 1500 × 250mm  
**Product thickness:** 2.5mm  
**Content / box:** 12/4.5m<sup>2</sup>



Installed area Fashion Oak with the Fashion Oak Cream example | lacquered, all around V4 joint



Fashion Oak Cream | PL092C | Elegant wood structure | lacquered, all around V4 joint



Fashion Oak Natural | PL091C | Elegant wood structure | lacquered, all around V4 joint



Fashion Oak Grey | PL093C | Elegant wood structure | lacquered, all around V4 joint

## wineo 1500 wood XL

**Installation type:** Glue  
**Format:** 1500 × 250mm  
**Product thickness:** 2.5mm  
**Content / box:** 12/4.5m<sup>2</sup>



Installed area Queen's Oak with the Queen's Oak Pearl example | lacquered, all around V4 joint



Queen's Oak Pearl | PL097C | Elegant wood structure | lacquered, all around V4 joint



Queen's Oak Amber | PL096C | Elegant wood structure | lacquered, all around V4 joint

## wineo 1500 wood XL

**Installation type:** Glue  
**Format:** 1500 × 250mm  
**Product thickness:** 2.5mm  
**Content / box:** 12/4.5m<sup>2</sup>



Installed area Western Oak with the Western Oak Cream example | lacquered, all around V4 joint



Western Oak Cream | PL094C | Elegant wood structure | lacquered, all around V4 joint



Western Oak Desert | PL095C | Elegant wood structure | lacquered, all around V4 joint

## wineo 1500 wood XL

**Installation type:** Glue  
**Format:** 1500 × 250mm  
**Product thickness:** 2.5mm  
**Content / box:** 12/4.5m<sup>2</sup>



Installed area Royal Chestnut with the Royal Chestnut Grey example | lacquered, all around V4 joint



Royal Chestnut Grey | PL084C | Fine wood structure | lacquered, all around V4 joint



Royal Chestnut Desert | PL085C | Fine wood structure | lacquered, all around V4 joint



Royal Chestnut Mocca | PL086C | Fine wood structure | lacquered, all around V4 joint

# wineo 1500 wood XL

**Installation type:** Glue  
**Format:** 1500 × 250mm  
**Product thickness:** 2.5mm  
**Content / box:** 12/4.5m<sup>2</sup>



Installed area Village Oak with the Village Oak Grey example | lacquered, all around V4 joint



Village Oak Grey | PL089C | Elegant wood structure | lacquered, all around V4 joint



Village Oak Cream | PL087C | Elegant wood structure | lacquered, all around V4 joint



Village Oak Brown | PL088C | Elegant wood structure | lacquered, all around V4 joint





## wineo 1500 stone XL

# BEST INGREDIENTS FOR MORE STYLE

Classic marble, modern copper and varying industrial designs come together with stylish decors to form the wineo 1500 stone XL. In the modern format 1000 × 500 mm the tiles create a very special atmosphere.

## wineo 1500 stone XL

**Installation type:** Glue  
**Format:** 1000 × 500 mm  
**Product thickness:** 2.5 mm  
**Content / box:** 10/5 m<sup>2</sup>

## wineo 1500 stone XL

**Installation type:** Glue  
**Format:** 1000 × 500 mm  
**Product thickness:** 2.5 mm  
**Content / box:** 10/5 m<sup>2</sup>



**Urban Copper** (Installed area) | PL103C | Soft structure




**Raw Industrial** (Installed area) | PL104C | Soft structure



**Grey Marble** (Installed area) | PL105C | Soft structure



**Just Concrete** (Installed area) | PL101C | Soft structure



**Carpet Concrete** (Installed area) | PL102C | Soft structure



**Scivaro Slate** (Installed area) | PL038C | Slate structure



**White Marble** (Installed area) | PL090C | Soft structure

# Bē

wellness & spa  
beautycare

Berlin  
Bielefeld  
Frankfurt  
Köln  
Leipzig  
München  
Potsdam  
Stuttgart



**wineo 1500**  
wood

## BEST INGREDIENTS FOR GOOD BUSINESS

Warm, natural, primal –  
wineo 1500 wood includes  
8 wood designs for every requirement.  
From classic oak and walnut to exotic  
wood designs for a warm and  
pleasant atmosphere.

## wineo 1500 wood

**Installation type:** Glue  
**Format:** 20 × 2 m  
**Product thickness:** 2.5 mm  
**Content / box:** 1/40 m<sup>2</sup>



**Floating Wood Snow** | PLR133C | Soft structure



**Floating Wood Sand** | PLR134C | Soft structure

## wineo 1500 wood

**Installation type:** Glue  
**Format:** 20 × 2 m  
**Product thickness:** 2.5 mm  
**Content / box:** 1/40 m<sup>2</sup>



**Napa Walnut Cream** | PLR135C | Fine wood structure



**Napa Walnut Brown** | PLR136C | Fine wood structure



## wineo 1500 wood

**Installation type:** Glue  
**Format:** 20 × 2 m  
**Product thickness:** 2.5 mm  
**Content / box:** 1/40 m<sup>2</sup>



Halifax Oak | PLR036C | Fine wood structure



Pacific Oak | PLR037C | Fine wood structure

## wineo 1500 wood

**Installation type:** Glue  
**Format:** 20 × 2 m  
**Product thickness:** 2.5 mm  
**Content / box:** 1/40 m<sup>2</sup>



Cottage Oak | PLR038C | Fine wood structure



Missouri Oak | PLR039C | Fine wood structure

## wineo 1500 wood

**Installation type:** Glue  
**Format:** 20 × 2 m  
**Product thickness:** 2.5 mm  
**Content / box:** 1/40 m<sup>2</sup>



**Newport Oak Natural** | PLR393C | Fine wood structure



**Newport Oak Brown** | PLR394C | Fine wood structure

## wineo 1500 wood

**Installation type:** Glue  
**Format:** 20 × 2 m  
**Product thickness:** 2.5 mm  
**Content / box:** 1/40 m<sup>2</sup>



**Durban Oak Taupe** | PLR391C | Fine wood structure



**Melbourne Oak Natural** | PLR395C | Fine wood structure

## wineo 1500 wood

**Installation type:** Glue  
**Format:** 20 × 2 m  
**Product thickness:** 2.5 mm  
**Content / box:** 1/40 m<sup>2</sup>



Halifax Oak Natural | PLR389C | Fine wood structure



Napa Walnut Rust | PLR388C | Fine wood structure

## wineo 1500 wood

**Installation type:** Glue  
**Format:** 20 × 2 m  
**Product thickness:** 2.5 mm  
**Content / box:** 1/40 m<sup>2</sup>



Halifax Oak Brown | PLR390C | Fine wood structure



Melbourne Oak Brown | PLR396C | Fine wood structure

# wineo 1500 wood

**Installation type:** Glue  
**Format:** 20 × 2 m  
**Product thickness:** 2.5 mm  
**Content / box:** 1/40 m<sup>2</sup>



Durban Oak Brown | PLR392C | Fine wood structure



Steel Grey  
 wineo 1500 chip | PLR023C  
 Durban Oak Brown  
 wineo 1500 wood | PLR392C




## wineo 1500 chip

# BEST INGREDIENTS FOR CONVINCING HIGHLIGHTS

Whether plainly coloured, strongly or slightly chipped, in muted beige and grey tones or as a colourful highlight: With 24 designs the wineo 1500 chip effectively makes its mark.

## wineo 1500 chip


**Installation type:** Glue  
**Format:** 20 × 2 m  
**Product thickness:** 2.5 mm  
**Content / box:** 1/40 m<sup>2</sup>



**Pure White** | PLR025C | Soft structure



**Pure White Stars** | PLR123C | Soft structure



**Sinai Sand** | PLR002C | Soft structure



**Sinai Sand Stars** | PLR130C | Soft structure



**Melange** | PLR003C | Soft structure



**Cappuccino** | PLR004C | Soft structure

## wineo 1500 chip

**Installation type:** Glue  
**Format:** 20 × 2 m  
**Product thickness:** 2.5 mm  
**Content / box:** 1/40 m<sup>2</sup>




**Light Grey** | PLR021C | Soft structure



**Steel Grey** | PLR023C | Soft structure




**Silver Grey** | PLR022C | Soft structure



**Silver Grey Stars** | PLR124C | Soft structure



**Midnight Grey** | PLR024C | Soft structure



**Midnight Grey Stars** | PLR126C | Soft structure

## wineo 1500 chip

**Installation type:** Glue  
**Format:** 20 × 2 m  
**Product thickness:** 2.5 mm  
**Content / box:** 1/40 m<sup>2</sup>



**Honey Mustard** | PLR128C | Soft structure



**Terracotta Dark** | PLR009C | Soft structure




**Red Rubin** | PLR011C | Soft structure



**Apple Green** | PLR185C | Soft structure



**Racing Green** | PLR019C | Soft structure



**Jungle Green** | PLR018C | Soft structure

## wineo 1500 chip


**Installation type:** Glue  
**Format:** 20 × 2 m  
**Product thickness:** 2.5 mm  
**Content / box:** 1/40 m<sup>2</sup>




**Purple Rain** | PLR013C | Soft structure




**Summer Sky** | PLR014C | Soft structure



**Navi Blue** | PLR129C | Soft structure



**Navi Blue Stars** | PLR131C | Soft structure



**Denim Blue Stars** | PLR132C | Soft structure



**Pure Black Stars** | PLR127C | Soft structure

## wineo 1500 chip

**Installation type:** Glue  
**Format:** 20 × 2 m  
**Product thickness:** 2.5 mm  
**Content / box:** 1/40 m<sup>2</sup>



**Tropical Orange** | PLR386C | Soft structure



**Cherry Red** | PLR387C | Soft structure



**Royal Blue** | PLR385C | Soft structure



**Cotton Beige** | PLR383C | Soft structure



**Chocolate Brown** | PLR384C | Soft structure



**Wheat Brown** | PLR379C | Soft structure

## wineo 1500 chip

**Installation type:** Glue  
**Format:** 20 × 2 m  
**Product thickness:** 2.5 mm  
**Content / box:** 1/40 m<sup>2</sup>



**Sunshine Yellow** | PLR377C | Soft structure




**Jade Green** | PLR373C | Soft structure



**Almond Beige** | PLR375C | Soft structure



**Powder Rose** | PLR374C | Soft structure



**Springtime Orange** | PLR378C | Soft structure



**Fountain Blue** | PLR376C | Soft structure



# wineo 1500 chip

**Installation type:** Glue  
**Format:** 20 × 2 m  
**Product thickness:** 2.5 mm  
**Content / box:** 1/40 m<sup>2</sup>




**Aloe Green** | PLR380C | Soft structure



**Ocean Blue** | PLR381C | Soft structure



**Rust Brown** | PLR382C | Soft structure



**Ocean Blue**  
 wineo 1500 chip | PLR381C  
**Melbourne Oak Brown**  
 wineo 1500 wood | PLR396C



**wineo 1500**  
fusion | fusion XL

## BEST INGREDIENTS FOR SUITABLE DESIGNS

Especially adapted to the needs of architects and planners, the wineo 1500 fusion offers the matching grey tone for all furnishing concepts. Whether light or dark tones, summerly warm or pleasantly cool – the 16 different designs distinguish themselves and integrate perfectly into the existing colour concept of your room.

wineo 1500 fusion is available as a roll (fusion) and as a tile (fusion XL). Thanks to our **match guarantee** you will always find the matching decor even for particularly challenging furnishing elements. Guaranteed.



**reddot** award 2019  
winner




# cool

# pure

# warm

# bright

one



one

two



two

three



three

four




four

# wineo 1500 fusion combinations

## BEST INGREDIENTS FOR CLASSY HIGHLIGHTS

The two graphic decors, flowers and ornaments, provide extra highlights. These were colour composed based on the decors in the fusion matrix. In this way, every colour row develops a light and a dark decor variant that you can combine perfectly with all decors from the fusion collection.

**We would be happy to advise you.**





cool

pure


warm

bright

flowers




ornaments



# BEST INGREDIENTS FOR SPECIAL REQUIREMENTS

Extraordinary assignments require extraordinary solutions. That is why wineo 1500 is also available in other special variants – always individually made to measure for the respective area of application.

PRODUCT	AREAS OF APPLICATION				
	wineo 1500	wineo 1500 customised	wineo 1500 safety	wineo 1500 rail	wineo 1500 sea
HEALTHCARE	✓	✓	✓		
APARTMENT BUILDING	✓	✓			
STORE BUILDING	✓	✓	✓		
HOTELS AND RESTAURANTS	✓	✓	✓		
EDUCATION AND PUBLIC BUILDINGS	✓	✓	✓		
MARITIME		✓			✓
RAILWAY		✓		✓	




## wineo 1500 customised

Be it the company logo in the conference room or abstract colours and patterns in the studio, with wineo 1500 customised your creativity will know no bounds. Design the floor you have always wanted, thereby creating your own unique and valuable product.





Light Grey  
wineo 1500 chip | PLR021C




## wineo 1500 safety

Whether it's freshly wiped or you are simply in a hurry, wineo 1500 safety ensures the greatest possible slip resistance with its special surface. It is R10 and A/B certified and is therefore ideal for hotels, hospitals, nursing care facilities, schools or your workplace.



## wineo 1500 rail

When thousands of people force themselves through the aisles of a train, that means maximum stress for the materials. To deal with these requirements, we have wineo 1500 rail. It is extremely long-lasting and meets all the related safety requirements.



## wineo 1500 sea

Modern shipbuilding and progressive offshore facilities require a great deal of technical knowledge as well as reliable and, above all, resilient technologies. With these specific requirements in mind, the flooring brand wineo has developed a special flooring solution: wineo 1500 sea. This product offers ideal attributes in the event of fire and fulfills all safety requirements in accordance with the current IMO regulations.

# PERFECT FIT ACCESSORIES

## SKIRTING BOARDS, EXTERNAL CORNERS AND FUSE WIRES

Particularly in sensitive areas such as healthcare, in which maximum cleanliness and hygiene are crucial, skirting boards and external corners are indispensable. They connect the wall and the floor perfectly, thereby creating a particularly neat and absolutely impermeable final sealing. Our prefabricated skirting boards and external corners for wineo PURLINE organic flooring are available in every design promoted via the collections and are always manufactured for you on an order basis. The associated PURLINE fuse wires for seamless welding, are also available for every design.



Detailed information can be found  
in our accessories brochure  
Art.-no. 20091021.



Download now:



### The available dimensions

skirting boards: 100 mm height x 100 mm depth x 2400 mm length

external corners: 100 mm height x 100 mm depth x 130 mm x 130 mm dimension



## SKIRTINGS

- decor matching MDF skirtings for all wineo floor coverings and universally usable skirtings MDF as well as plastic /aluminium
- installation heights from 60mm to 100mm
- plastic mounting clips included in the range of accessories; alternatively glue or tack
- self-adhesive corner elements for easy installation

## UNDERLAY MATERIAL

We recommend using our polyurethane underlay material with wineo 1500.

The basis is provided by ecuran, a high-performance composite material that is manufactured primarily from plant-based oils such as canola oil or castor oil and naturally-occurring mineral components such as chalk.

- **fast, energy-efficient distribution of ground heat**
- **excellent noise reduction with hard and soft floor coverings**
- **long-life performance of at least 30 years**
- **outstanding residual indentation behaviour**
- **sustainable raw materials**
- **without chlorine, plasticisers or solvents**



Find out more about  
our underlay mats:



[www.blauer-engel.de/uz156](http://www.blauer-engel.de/uz156)








# SERVICE



## A WARM WELCOME!

Would you like an individual consultation in the wineo workspace or simply be inspired by the innovative and beautiful floors?

We will be happy to take the time to show you the whole wineo variety.



## EN.WINEO.DE

Even more information is available on our website:

- dealer portal with direct ordering option
- our top reference projects
- tender specifications
- technical data sheets
- cleaning and installation instructions
- find a dealer
- video portal with lots of tips
- newsletter registration
- and much more

## WINEO FLOOR VIEWER










Any wineo floor can be simulated in your own home in an instant with our wineo Floor Viewer. The ideal way to choose the perfect flooring for you.

Test the wineo Floor Viewer now at [floorviewer.wineo.de](https://floorviewer.wineo.de)












# WE FOCUS ON TRANSPARENCY

## Environmental certifications






	<p><b>cradle to cradle®</b></p> <p>The cradle to cradle® certification confirms the utilisation of environmentally safe, healthy and reusable materials (technical reutilisation) and the use of solar power or other regenerative sources of energy, together with responsible water stewardship and strategies adopted by a company to embrace its responsibility to society.</p>	✓
	<p><b>Blue Angel (Blauer Engel)</b></p> <p>The "Blue Angel" guarantees that our products and services fulfil high requirements placed on environmental, health and usage properties. Criteria are compiled for each product group, which are checked every three to four years by the Federal Environment Agency.</p> <p><a href="http://www.blauer-engel.de/uz120">www.blauer-engel.de/uz120</a>  <a href="http://www.blauer-engel.de/uz156">www.blauer-engel.de/uz156</a>  <a href="http://www.blauer-engel.de/uz176">www.blauer-engel.de/uz176</a></p>	✓
	<p><b>eco-INSTITUT-label</b></p> <p>The eco-INSTITUT label confirms that a product complies with certain environmentally friendly and health standards. The label signals to consumers that the certified product is environmentally friendly and has been tested for harmful substances, which promotes transparency and trust with regard to sustainability and health aspects.</p>	✓
	<p><b>Austrian eco-label (Österreichisches Umweltzeichen)</b></p> <p>The "Österreichisches Umweltzeichen" (Austrian eco-label) assesses products from quality, health-related and ecological standpoints. Basically, products can only be certified if they are harmless health-wise. The fulfilment of the criteria is checked every four years.</p>	✓
	<p><b>Greenguard</b></p> <p>The Greenguard certificate ensures that a product fulfils the strictest and most comprehensive requirements for emissions of Volatile Organic Compounds (VOCs) into the air.</p>	✓
	<p><b>Declare</b></p> <p>Voluntary self-disclosure programme aimed at transforming the building materials industry into a healthier and more environmentally friendly product through transparency of ingredients used. By participating in Declare, manufacturers are obligated to disclose all ingredients.</p>	✓
	<p><b>M1</b></p> <p>Just like the "Blue Angel" quality mark in Germany, the M1 seal in the Finnish market labels our products as environmentally friendly, health-friendly and consumer-friendly. The focus is on emissions of Volatile Organic Compounds (VOCs).</p>	✓
	<p><b>A+</b></p> <p>Just like the "Blue Angel" in Germany, the A+ seal identifies our products as ecological, healthy and user-friendly in the French market.</p>	✓
	<p><b>TFI-TÜV PROFICERT PREMIUM for Multi-Layer</b></p> <p>The TFI (Textiles &amp; Flooring Institute GmbH) and the TÜV Hessen evaluate products based on qualitative, health and ecological principals. Fundamentally, only products that are considered harmless to health can be certified.</p>	✓

## Environmental certifications

	<p><b>KfB</b></p> <p>Award from the competence centre for dynamic processes at Bielefeld University of Applied Sciences (FH). The flooring product Purline has passed the dynamic standard examination of rolling behaviour in accordance with the KfB roadmap.</p>	✓
	<p><b>eco-bau Switzerland (eco-bau Schweiz)</b></p> <p>Eco-Bau assesses the ecological aspects of building materials and services. It encompasses all of the significant environmental effects during the entire lifespan of the materials. The assessment is made on the basis of the following criteria: conservation of natural resources, energy for producing materials, solvent emissions, presence of environmentally and health-damaging components, emission of heavy metals and other damaging substances.</p>	✓
	<p><b>FloorScore®</b></p> <p>With SCS Global Services' FloorScore® certificate program manufacturers of floor coverings can assess the conformity of their products with the emission requirements in the U.S. but also worldwide utilized building evaluation systems, such as LEED clearly.</p>	✓
<b>Building certification/Product declaration</b>		
	<p><b>BREEAM</b></p> <p>The British sustainability certificate for development projects is used in 15 other countries.</p>	✓
	<p><b>DGNB</b></p> <p>Certification system of the German Sustainable Building Council and the Federal Ministry of Transport, Building and Urban Affairs. Evaluates a building's quality over its entire life cycle and is internationally applicable.</p>	✓
	<p><b>LEED</b></p> <p>Rating system of the US Green Building Council. It considers the regional and local criteria according to global standards. The use of building materials with cradle to cradle proof is evaluated with bonus points.</p>	✓
	<p><b>WELL</b></p> <p>The WELL Building Standard (WELL) focuses on health and well-being of the people within in the building.</p>	✓
	<p><b>EPD</b></p> <p>The environmental product declarations is a transparency tool for the sustainability valuation of products. It is the basis for sustainability calculations for buildings.</p>	✓
<b>Information platforms</b>		
	<p><b>Heinze</b></p> <p>Germany's leading information platform for building products, company profiles and architectural projects.</p>	✓

**SUSTAINABLE FOR NATURE.  
WELLBEING FOR PEOPLE.**

# COLLECTION OVERVIEW


Collection	wineo 1500 wood chip fusion safety	wineo 1500 wood XS	wineo 1500 wood L	wineo 1500 wood XL	wineo 1500 stone XL fusion XL
Installation type	 roll to glue	 plank to glue	 plank to glue	 plank to glue	 tile to glue
Utilisation classes   EN ISO 10874	23/34/43	23/34/43	23/34/43	23/34/43	23/34/43
Format	20 × 2 m	600 × 100 mm	1200 × 200 mm	1500 × 250 mm	1000 × 500 mm
Product thickness	2.5 mm	2.5 mm	2.5 mm	2.5 mm	2.5 mm
Weight	3.45 kg/m <sup>2</sup>	3.6 kg/m <sup>2</sup>	3.45 kg/m <sup>2</sup>	3.45 kg/m <sup>2</sup>	3.45 kg/m <sup>2</sup>
Content/box	1/40 m <sup>2</sup>	28/1.68 m <sup>2</sup>	20/4.8 m <sup>2</sup>	12/4.5 m <sup>2</sup>	10/5 m <sup>2</sup>
Boxes/pallet	6/240 m <sup>2</sup>	144/241.92 m <sup>2</sup>	48/230.4 m <sup>2</sup>	52/234 m <sup>2</sup>	50/250 m <sup>2</sup>
Staining / chemical resistance EN ISO 26987	very good resistance with regards to concentration and exposure time				
Reaction to fire   EN 13501-1	C <sub>n</sub> - s1				
Anti slip category   DIN 51130	R9 (safety R10)				
Light fastness   EN ISO 105-B02	~ 7				
Residual indentation   EN ISO 24343-1	≤ 0.10 mm	≤ 0.10 mm	≤ 0.10 mm	≤ 0.10 mm	≤ 0.10 mm
Slip resistance   EN 13893	μ ≥ 0.30 DS				
Dimensional stability   EN ISO 23999	≤ 0.15 %				
Flexural behaviour   EN ISO 24344	≥ 20 mm				
Underfloor heating	Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperature of 27 °C.				
Thermal resistance   ISO 12667	~ 0.01 (m <sup>2</sup> K)/W	~ 0.01 (m <sup>2</sup> K)/W	~ 0.01 (m <sup>2</sup> K)/W	~ 0.01 (m <sup>2</sup> K)/W	~ 0.01 (m <sup>2</sup> K)/W
Effect of a castor chair   EN 425/ISO 4918	Typ W				
Impact sound reduction   EN ISO 10140	~ 4 dB	~ 4 dB	~ 4 dB	~ 4 dB	~ 4 dB
Effect of a furniture leg   EN 424	without damages				
Wear resistance   EN 660-2	Group T				
Anti-static properties   EN 1815	≤ 2 kV				
Guarantee	en.wineo.de/service/guarantee				




Windmüller GmbH offers a manufacturer's lifetime warranty for PURLINE organic flooring in the residential sector. If an underlay material is used, the warranty is only valid if a recommended wineo PERFECT FIT underlay mat is used. For more information, please visit: [en.wineo.de/service/guarantee](http://en.wineo.de/service/guarantee)




Utilisation class 23:  
Domestic area  
with intensive usage



Utilisation class 41:  
Light industry sector  
with moderate usage



Utilisation class 34:  
Very heavy-duty use  
in the commercial sector



Utilisation class 43:  
Heavy-duty use  
in the light industrial sector

Alle decors shown in this brochure are reproductions. Windmüller GmbH provides no guarantee with regard to mistakes, printing errors and technical changes.



**windmüller**  
PIONEER THINKING

## FORWARD THINKING. ALWAYS.

That is why we are constantly working on innovations and products that can do more. In recent years, we have been able to bring several new products to market which can now be found in many households and public buildings. Worldwide.

For generations, Windmüller has been known for its dedication to future development and collaborative partnerships. We impress people, companies and markets all over the world with our flooring ideas, materials and technologies.



“Our products are always as sustainable as current technology allows. And we are getting better at it every day. Because striving for sustainability is what drives us.”

**Matthias Windmüller**  
CEO Windmüller GmbH

**Windmüller GmbH**

Nord-West-Ring 21

D-32832 Augustdorf

Tel.: +49 (0) 52 37 609 - 0

Fax: +49 (0) 52 37 609 - 309

info@wineo.de

**www.wineo.de**

Handed over by:

Member of

**FEB** ERFMI. DGNB

**wineo**