


## Technical information

### Luxury Tiles (LT) Floor's structure:

1. PU Protective coating
2. Wear layer PET
3. Print layer
4. Middle layer
5. Aucoustic layer



### Measurement specification (standard products):


#### Wood

Size of the tiles: 218 mm × 1210 mm  
 Total thickness: 6 mm  
 M<sup>2</sup> tiles per package: 2,1 m<sup>2</sup>



#### Stone

Size of the tiles: 304 mm × 609 mm  
 Total thickness: 6 mm  
 M<sup>2</sup> tiles per package: 1,86 m<sup>2</sup>



VOC	PASS	
Wear layer	EN 429	0,3 mm PET
Total weight	EN 430	8,5 kg/m <sup>2</sup>
Classification	EN 685	33
Chemical resistance	EN 423	Pass
Office chair wheel	ISO 4918:2016	Pass
Indentation resistance	EN 433	≤ 0,05 mm
Dimensional stability	ISO 23999-2021	Pass
Flexibility	EN 435	Pass
Wear resistance	EN 660	Group T reduced thickness 0,068 mm
Slip protection	DIN 51130	R9
Noise damping	DIN 52210	18 dB
Light fastness	ISO 2105 B02	> 6
On underfloor heating		Yes, max +27°
Fire rating	EN 13501-1	Bfl - S1
Friction test	EN 13893:2002	Pass